

Airtime

Published : 2011-03-18
License : GPLv3

Table of Contents

Introduction

1	Airtime for Broadcasters	2
---	--------------------------	---

Installation

2	Preparing the server	5
3	Manual installation	9
4	Setting the server time	13
5	Using the import script	15

Using Airtime

6	Getting started	18
7	Managing users	20
8	Now playing	22
9	Add audio	24
10	Playlist builder	27
11	Calendar	31
12	Help	38


Appendix

13	Time zones	40
14	About this manual	48

INTRODUCTION

Airtime for Broadcasters

Airtime is the open broadcast software for scheduling and remote station management. Web browser access to the station's media, multi-file upload and automatic metadata verification features are coupled with a collaborative on-line scheduling calendar and playlist management. The scheduling calendar is managed through an easy-to-use interface and triggers playout with sub-second precision.



Date	Start	End	Duration	Song	Artist	Album	Playlist	Show
2011-02-23	12:12:50.11	12:16:35.86	00:03:45.75	Unlabeled	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:16:35.86	12:19:33.26	00:02:57.39	Genika Gai	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:19:33.26	12:21:35.98	00:02:02.72	Tangerine	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:21:35.98	12:24:41.32	00:03:05.33	SnakeOut	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:24:41.32	12:28:08.78	00:03:27.46	Panic	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:28:08.78	12:31:26.16	00:03:17.38	Wanted	Offi Gal	PANIC	Test show 3	Show 3
2011-02-23	12:31:26.16	12:33:36.79	00:02:10.63	Last Days Of Summer	Peter Rudenko		Test show 3	Show 3
2011-02-23	12:33:36.79	12:40:08.24	00:06:31.44	Fatness	Pestovska	Fatness	Test show 3	Show 3
2011-02-23	12:40:08.24	12:43:16.34	00:03:08.10	dance cleopatra vinyl	ZamaSka	demo	Test show 3	Show 3
2011-02-23	12:43:16.34	12:46:23.88	00:03:07.53	catching the sun	ZamaSka	demo	Test show 3	Show 3
2011-02-23	12:46:23.88	12:49:30.32	00:03:06.44	pandemie ska vinyl	ZamaSka	demo	Test show 3	Show 3
2011-02-23	12:49:30.32	12:54:13.67	00:04:43.35	germans are coming vinyl	ZamaSka	demo	Test show 3	Show 3

Airtime has been intended to provide a solution for a wide range of broadcast projects, from community to public and commercial stations. The scalability of Airtime allows implementation in a number of scenarios, ranging from an unmanned broadcast unit accessed remotely through the Internet, to a local network of machines accessing a central Airtime storage system. Airtime supports the playout of files in both the commonly used MP3 format and the open, royalty-free equivalent Ogg Vorbis.


Airtime manages the Liquidsoap stream generator, which is at the heart of the system. Liquidsoap accesses the Airtime media archive, stored in a PostgreSQL database. Editors and station controllers can use Airtime to build playlists and manage files (upload, add metadata, manage advertisements) inside the station or via the Internet, using a standard web browser such as Mozilla Firefox or Internet Explorer.

The scheduler in Airtime has a calendar view, organized by months, weeks and days. Here the program editors can schedule playlists and streams for their broadcast station. In some scenarios, the transmitter is situated outside the reach of the broadcaster and all program management has to be maintained through the web interface. Possible reasons for this scenario might be of a pragmatic nature (running many stations from one central office due to limited human resources) or an emergency (running a transmitter in a crisis area without putting staff at risk).

Example system

Combining Airtime, the Liquidsoap stream generator and PostgreSQL storage, you can supply a broadcast station with all the functionality needed for automation.

In the diagram below, the media files are stored on a separate PostgreSQL machine accessible through the local network. Liquidsoap outputs streams to both the transmitter and a streaming media server. The machine running Airtime is behind a firewall because it is connected both to the local network, and to the Internet for remote access. This enables Airtime to offer password-protected access to the media database and scheduling from both inside and outside the studio building.



INSTALLATION

Preparing the server

The following instructions assume that you have root access (*sudo* on Ubuntu) to a GNU/Linux server, and are familiar with basic command line tasks.

The recommended Airtime server platform is Ubuntu 10.04 'Lucid Lynx' LTS. Debian 6.0 'squeeze' is also a good option. The server should have at least a 1GHz processor and 512MB of RAM. The Airtime installation does not use much disk space, but you should allow plenty of storage capacity for the media archive. A hot-swap RAID array is recommended for the media archive, in case of disk failure. You should also consider a UPS or other battery powered system to offer some protection against short-term power failures.

If you intend that your Airtime server will have a direct audio output to a broadcast transmitter or a separate stream encoder, your server machine must have a soundcard supported by an ALSA driver. Almost all standard soundcards have ALSA drivers built into the Linux kernel, which do not need to be installed separately. If in doubt about driver support for your soundcard, check the ALSA soundcard matrix at: <http://www.alsa-project.org/main/index.php/Matrix:Main>

If your Airtime machine will only be used to stream to an Icecast streaming media server, you do not require a soundcard to be installed on the server side. This option is suitable for Airtime installations at your ISP's datacenter, remote from any transmitter.


The Airtime web administration interface is intended to work with any browser, on any desktop or mobile platform. The recommended web browser is Mozilla Firefox 3.6.

Install dependencies

When installing on an Ubuntu server, a few of the packages that Airtime relies on are in the Ubuntu *universe* or *multiverse* repositories. If either of these repositories is disabled, you can enable them in the */etc/apt/sources.list* file, by opening the *nano* editor in your server's console with the command:

```
$ sudo nano /etc/apt/sources.list
```

Find the lines which begin *deb* and end with *lucid universe* or *lucid-updates universe*, adding *multiverse* to the end of these lines, if it is not there already. The multiverse repository is required for the *libmp3lame0* library, which is an MP3 encoder.



```
GNU nano 2.2.2 File: /etc/apt/sources.list
# deb cdrom:[Ubuntu 10.04 LTS 'Lucid Lynx' - Release amd64 (20100429)]/ lucid main restricted
# See http://help.ubuntu.com/community/UpgradeNotes for how to upgrade to
# newer versions of the distribution.
deb http://gb.archive.ubuntu.com/ubuntu/ lucid main
## Major bug fix updates produced after the final release of the
## distribution.
deb http://gb.archive.ubuntu.com/ubuntu/ lucid-updates main
## N.B. software from this repository is ENTIRELY UNSUPPORTED by the Ubuntu
## team. Also, please note that software in universe WILL NOT receive any
## review or updates from the Ubuntu security team.
deb http://gb.archive.ubuntu.com/ubuntu/ lucid universe multiverse
deb http://gb.archive.ubuntu.com/ubuntu/ lucid-updates universe multiverse
## N.B. software from this repository is ENTIRELY UNSUPPORTED by the Ubuntu
## team, and may not be under a free licence. Please satisfy yourself as to
## your rights to use the software. Also, please note that software in
## multiverse WILL NOT receive any review or updates from the Ubuntu
## security team.

^G Get Help  ^O WriteOut  ^R Read File  ^V Prev Page  ^K Cut Text   ^C Cur Pos
^X Exit      ^J Justify   ^W Where Is   ^N Next Page  ^U UnCut Text ^T To Spell
```

The exact repository mirror URLs in your *sources.list* file will differ from the above screenshot, depending on your location.

For a Debian server, you can install the *lame* library package by adding the following repository to the */etc/apt/sources.list* file:

```
deb http://www.debian-multimedia.org squeeze main non-free
```

Press Ctrl+O (the Ctrl key and the letter O together) to save the file, then Ctrl+X to exit the *nano* editor. Then reload the package list with:

```
$ sudo apt-get update
```

This command fetches lists of the latest packages from the repositories that you have configured for your server.

```
daniel@office:~$ sudo apt-get update
Hit http://security.ubuntu.com lucid-security Release.gpg
Hit http://gb.archive.ubuntu.com lucid Release.gpg
Ign http://security.ubuntu.com/ubuntu/ lucid-security/main Translation-en_GB
Hit http://gb.archive.ubuntu.com/ubuntu/ lucid/main Translation-en_GB
Ign http://security.ubuntu.com/ubuntu/ lucid-security/universe Translation-en_GB
Hit http://gb.archive.ubuntu.com/ubuntu/ lucid/universe Translation-en_GB
Hit http://security.ubuntu.com lucid-security Release
Hit http://gb.archive.ubuntu.com/ubuntu/ lucid/multiverse Translation-en_GB
Hit http://security.ubuntu.com lucid-security/main Packages
Hit http://gb.archive.ubuntu.com lucid-updates Release.gpg
Hit http://security.ubuntu.com lucid-security/universe Packages
Ign http://gb.archive.ubuntu.com/ubuntu/ lucid-updates/main Translation-en_GB
Ign http://gb.archive.ubuntu.com/ubuntu/ lucid-updates/universe Translation-en_GB
Ign http://gb.archive.ubuntu.com/ubuntu/ lucid-updates/multiverse Translation-en_GB
Hit http://gb.archive.ubuntu.com lucid Release
Hit http://gb.archive.ubuntu.com lucid-updates Release
Hit http://gb.archive.ubuntu.com lucid/main Packages
Hit http://gb.archive.ubuntu.com lucid/universe Packages
Hit http://gb.archive.ubuntu.com lucid/multiverse Packages
Hit http://gb.archive.ubuntu.com lucid-updates/main Packages
Hit http://gb.archive.ubuntu.com lucid-updates/universe Packages
Hit http://gb.archive.ubuntu.com lucid-updates/multiverse Packages
Reading package lists... Done
daniel@office:~$
```

Next, install the list of dependencies for Airtime. For example, on Ubuntu 10.04 (Lucid Lynx) LTS you could enter the command:

```
$ sudo apt-get install apache2 daemontools daemontools-run icecast2 \
libao-ocaml libapache2-mod-php5 libcamomile-ocaml-dev libesd0 \
libmad-ocaml libmp3lame0 libportaudio2 libsamplerate0 libsoundtouch-ocaml \
libtaglib-ocaml libvorbis-ocaml-dev multitail odbc-postgresql \
oggvideotools openssl php-pear php5-gd php5-pgsql poc-streamer \
postgresql pwgen python python-configobj python-mutagen unzip
```

The final dependency to install is *phing* (note that you must use the version number shown):

```
$ sudo pear channel-discover pear.phing.info
$ sudo pear install phing/phing-2.4.2
```

Remove PulseAudio

The PulseAudio sound server is not compatible with Airtime. To remove it from an Ubuntu machine, type the following command:


```
$ sudo apt-get purge pulseaudio
```

Removing the *pulseaudio* package on a desktop Ubuntu machine may force the removal of the *ubuntu-desktop* metapackage. However, this metapackage is only on the system for managing upgrades; removing it does not remove the GNOME desktop.

After removing PulseAudio, if your Airtime machine has a desktop and a soundcard, you can install a mixer applet which can control the ALSA soundcard driver directly, such as *gnome-alsamixer*:

```
$ sudo apt-get install gnome-alsamixer
```

On a server with a soundcard but without a desktop, you can control sound output levels using the command line program *alsamixer*. This package should already be installed on an Ubuntu machine with a soundcard.



Configure PHP

Edit the *php.ini* file to change PHP settings for the server to those that Airtime requires.

```
$ sudo nano /etc/php5/apache2/php.ini
```

```
GNU nano 2.2.2 File: /etc/php5/apache2/php.ini

[PHP]
;
; About php.ini
;
; PHP's initialization file, generally called php.ini, is responsible for
; configuring many of the aspects of PHP's behavior.
;
; PHP attempts to find and load this configuration from a number of locations.
; The following is a summary of its search order:
; 1. SAPI module specific location.
; 2. The PHPRC environment variable. (As of PHP 5.2.0)
; 3. A number of predefined registry keys on Windows (As of PHP 5.2.0)
; 4. Current working directory (except CLI)
; 5. The web server's directory (for SAPI modules), or directory of PHP
; (otherwise in Windows)
; 6. The directory from the --with-config-file-path compile time option, or the
; Windows directory (C:\windows or C:\winnt)
; See the PHP docs for more specific information.
Search: post_max_size
^G Get Help ^Y First Line ^T Go To Line ^W Beg of Par ^J FullJstify ^B Backwards
^C Cancel ^V Last Line ^R Replace ^O End of Par ^C Case Sens ^R Regexp
```

This is a long file, so use the search tool (press Ctrl+W) to find the particular lines that you're looking for. The recommended initial settings for Airtime are:

```
memory_limit = 256M

request_order = "GPC"

post_max_size = 150M

upload_max_filesize = 150M

upload_tmp_dir = /tmp

session.gc_probability = 0
```

If any of the above lines are commented out with a semi-colon at the beginning, you will need to remove that semi-colon for the setting to work.

You also need to set the time zone that Airtime will display. Find the line in the *php.ini* file which begins *date.timezone*, remove the semi-colon comment if present, and add the required time zone to the end of the line. For example:

```
date.timezone = "America/Toronto"
```

The time zone value should be in quotes, as above. You can find the correct value for your server's time zone in the appendix of this manual.

Press Ctrl+O to save the *php.ini* file, then Ctrl+X to exit the *nano* editor.

Manual installation

The latest version of the Airtime installer is available at:

http://www.sourcefabric.org/en/products/airtime_download/

For example, to download version 1.6.1 from SourceForge in the server console you could enter the command:

```
$ wget http://sourceforge.net/projects/airtime/files/airtime-1.6.1-GA.tar.gz
```

```
daniel@office:~/64studio/airtime$ wget http://sourceforge.net/projects/airtime/files/airtime-1.6.1-GA.tar.gz
--2011-03-01 13:27:12-- http://sourceforge.net/projects/airtime/files/airtime-1.6.1-GA.tar.gz
Resolving sourceforge.net... 216.34.181.60
Connecting to sourceforge.net|216.34.181.60|80... connected.
HTTP request sent, awaiting response... 302 Found
Location: http://sourceforge.net/projects/airtime/files/airtime-1.6.1-GA.tar.gz/download [following]
--2011-03-01 13:27:14-- http://sourceforge.net/projects/airtime/files/airtime-1.6.1-GA.tar.gz/download
Reusing existing connection to sourceforge.net:80.
HTTP request sent, awaiting response... 302 Found
Location: http://downloads.sourceforge.net/project/airtime/airtime-1.6.1-GA.tar.gz?r=&ts=1298986037&use_mirror=switch [following]
--2011-03-01 13:27:15-- http://downloads.sourceforge.net/project/airtime/airtime-1.6.1-GA.tar.gz?r=&ts=1298986037&use_mirror=switch
Resolving downloads.sourceforge.net... 216.34.181.59
Connecting to downloads.sourceforge.net|216.34.181.59|80... connected.
HTTP request sent, awaiting response... 302 Found
Location: http://switch.dl.sourceforge.net/project/airtime/airtime-1.6.1-GA.tar.gz [following]
--2011-03-01 13:27:15-- http://switch.dl.sourceforge.net/project/airtime/airtime-1.6.1-GA.tar.gz
Resolving switch.dl.sourceforge.net... 130.59.138.21
Connecting to switch.dl.sourceforge.net|130.59.138.21|80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 180724646 (172M) [application/x-gzip]
Saving to: `airtime-1.6.1-GA.tar.gz'

2% [>] 4,355,494 426K/s eta 4m 58s
```

Unzip the file you have just downloaded to the installation directory `/var/lib/airtime/` with the following command:

```
$ sudo tar -xvzf airtime-1.6.1-GA.tar.gz -C /var/lib/
```

Change the ownership of the installation directory to the *root* user so that it is more secure:

```
$ sudo chown -R root.root /var/lib/airtime/
```

Configure Apache

Check that the Apache web server modules that Airtime requires are enabled:

```
$ sudo a2enmod php5 rewrite
```

The server should respond:

```
Module php5 already enabled
Module rewrite already enabled
```

Next, create the Airtime virtual host configuration file for Apache:

```
$ sudo nano /etc/apache2/sites-available/airtime
```

and enter the information below, substituting your system administrator's email address for *admin@example.com*. Make sure you set the *DocumentRoot* and *Directory* paths correctly. This should match the *public* sub-directory of the installation directory that you unzipped the Airtime tarball into, such as `/var/lib/airtime/public` in this example.

```
<VirtualHost *:80>
    ServerAdmin admin@example.com
    DocumentRoot /var/lib/airtime/public

    SetEnv APPLICATION_ENV "development"

    <Directory /var/lib/airtime/public>
        DirectoryIndex index.php
        AllowOverride all
        Order allow,deny
```

```

    Allow from all
  </Directory>
</VirtualHost>

```

Press Ctrl+O to save the file, then Ctrl+X to exit the *nano* editor. Then enter the command:

```
$ sudo a2ensite airtime
```

The server should respond:

```

Enabling site airtime.
Run '/etc/init.d/apache2 reload' to activate new configuration!

```

As suggested by the output of the command above, reload the web server configuration.


```
$ sudo /etc/init.d/apache2 reload
```

The server should respond:

```
* Reloading web server config apache2
```

Enable Icecast

Before you run the Icecast streaming media server for the first time, edit the file */etc/icecast2/icecast.xml* to change the default *<source-password>*, *<relay-password>* and *<admin-password>* values from *'hackme'* to something more secure.



```

GNU nano 2.2.2      File: /etc/icecast2/icecast.xml

    it also significantly increases latency between the source
    client and listening client. For low-latency setups, you
    might want to disable this. -->
  <burst-on-connect>1</burst-on-connect>
  <!-- same as burst-on-connect, but this allows for being more
       specific on how much to burst. Most people won't need to
       change from the default 64k. Applies to all mountpoints -->
  <burst-size>65535</burst-size>
</limits>

<authentication>
  <!-- Sources log in with username 'source' -->
  <source-password>hackme</source-password>
  <!-- Relays log in username 'relay' -->
  <relay-password>hackme</relay-password>

  <!-- Admin logs in with the username given below -->
  <admin-user>admin</admin-user>
  <admin-password>hackme</admin-password>
</authentication>

<!-- set the mountpoint for a shoutcast source to use, the default if not
     specified is /stream but you can change it here if an alternative is

```

Then set up the Icecast server to start automatically:

```
$ sudo nano /etc/default/icecast2
```

by setting the value of *ENABLE* to *true* on the last line of this file:

```
ENABLE=true
```

Save and close the file with Ctrl+O and Ctrl+X, then start Icecast:

```
$ sudo service icecast2 start
```

The server should respond:

```

Starting icecast2: Starting icecast2
Detaching from the console
icecast2.

```

Set up and install Airtime

In the Liquidsoap configuration file */var/lib/airtime/pypo/scripts/lq_config.liq*, set the value of *icecast_pass* to the *<source-password>* value that you set in the Icecast configuration file:

```
$ sudo nano /var/lib/airtime/pypo/scripts/ls_config.liq
```

```
GNU nano 2.2.2 File: /var/lib/airtime/pypo/scripts/ls_config.liq
archive_dir = "/opt/pypo/archive/"

# list pointing to the current couchcaster mountpoint
couchcaster_list = "http://vdeb.openbroadcast.ch/mod/wl/api/pypo/current_couchcaster"

#####
# stream settings #
#####
icecast_host = "127.0.0.1"
icecast_port = 8000
icecast_pass = "hackme"

# mountpoints
mount_point_mp3 = "airtime.mp3"
mount_point_vorbis = "airtime.ogg"

# mount intra is used for scheduler >>> fallback stream
mount_intra = "pypo_intra"

# intra-LS streaming (no icecast here)
intra_host = "127.0.0.1"
intra_port = 9000
intra_pass = "hackme"

icecast_url = "http://airtime.sourcefabric.org"
icecast_description = "Airtime Radio!"
icecast_genre = "genre"

output_sound_device = false
output_icecast_vorbis = true
output_icecast_mp3 = true

^G Get Help      ^O WriteOut      ^R Read File     ^Y Prev Page     ^K Cut Text      ^C Cur Pos
^X Exit          ^J Justify       ^W Where Is      ^V Next Page     ^U UnCut Text    ^T To Spell
```

You can also configure the values of *mount_point_mp3*, *mount_point_vorbis*, *icecast_url*, *icecast_description*, and *icecast_genre* to suit your station.

If you require direct output to an ALSA soundcard device on the Airtime server, in addition to the Icecast stream, change the value of *output_sound_device* from the default of *false* to *true*:

```
output_sound_device = true
```

If you do not require an Icecast stream in either Ogg Vorbis or MP3 format, you can set the values of *output_icecast_vorbis* or *output_icecast_mp3*, respectively, to *false*. Then save and close the file with Ctrl+O and Ctrl+X.

Optionally, you may wish to edit the file */var/lib/airtime/application/configs/config.php* to set the directory where Airtime media files are stored. For example, you may wish to store media on a RAID array which is not part of the server's root filesystem.

```
$ sudo nano /var/lib/airtime/application/configs/config.php
```

Find the line which begins *\$baseFilesDir* and change the directory path to the one that you require, for example:

```
$baseFilesDir = __DIR__.' /mnt/raid10/media/';
```

In the same file, you can set the URL which will be used to access your Airtime server from outside your local network, if you choose to enable that option. Find the line in the *config.php* file which begins *'storageUrlHost'* and change the domain name from the default of *localhost*. For example:

```
'storageUrlHost' => 'airtime.example.com',
```

You can also set the web server port and the user name that the web server runs as here, if you are using non-standard settings. Save and close the file with Ctrl+O and Ctrl+X.

```
GNU nano 2.2.4      File: conf.php      Modified
Ctrl+O
define('AIRTIME_VERSION', '1.7.0 alpha');
define('AIRTIME_COPYRIGHT_DATE', '2010-2011');

// These are the default values for the config.
global $CC_CONFIG;
$values = load_airtime_config();

// =====
// START CUSTOMIZING HERE
// =====

// Set the location where you want to store all of your audio files.
//
// For example:
// $baseFilesDir = '/home/john/radio-files';
$baseFilesDir = __DIR__ . '/mnt/raid10/media/';

$CC_CONFIG = array(

    // Set the URL of your installation
    'storageUrlHost' => 'localhost',
    'storageUrlPort' => 80,

    // Name of the web server user
    'webServerUser' => 'www-data',

// =====
// STOP CUSTOMIZING HERE
//
// You don't need to touch anything below this point.
// =====

^G Get Help      ^O WriteOut      ^R Read File     ^Y Prev Page     ^K Cut Text      ^C Cur. Pos
^X Exit          ^J Justify       ^W Where Is      ^V Next Page     ^U UnCut Text    ^T To Spell
```

Then enter the following commands to create the Airtime databases, tables, and directories:

```
$ cd /var/lib/airtime/install/
$ sudo php airtime-install.php
```

Finally, reboot your server so that *daemontools* can initialize correctly.

Setting the server time

Accurate time keeping on your server is vital for optimal Airtime performance. You can confirm that the date and time of your server are set correctly with the *date* command:

```
$ date
```

The server should respond with the date, time, time zone and year in a format similar to the following example:

```
Mon Mar 7 14:59:17 GMT 2011
```

The time zone reported should match the continent and city that you set in the *php.ini* file during Airtime installation, such as *GMT* in the example above matching *Europe/London*. If not, see the section **Adjusting the server time zone** below.

Although it is possible to set the date and time of the server manually, this is not recommended because the server clock can drift over time, compromising the accuracy of your broadcast schedule. If your Airtime server is permanently connected to the Internet, you can synchronize your server to a time server with the *ntp* program. If *ntp* is not yet installed, you can enter the following command on Debian or Ubuntu:

```
$ sudo apt-get install ntp
```

Optionally, open the *ntp* configuration file in the *nano* editor to add further time server names:

```
$ sudo nano /etc/ntp.conf
```

On Ubuntu GNU/Linux, the default time server is *ntp.ubuntu.com*, but there are many other time servers available on the public Internet, including the group of servers listed at <http://www.pool.ntp.org/> for each country. Using a variety of NTP servers located closely to your Airtime server will produce the most accurate results. For example, for a server in the United Kingdom you could use the following list:

```
# You do need to talk to an NTP server or two (or three).
server ntp.ubuntu.com
server 0.uk.pool.ntp.org
server 1.uk.pool.ntp.org
server 2.uk.pool.ntp.org
server 3.uk.pool.ntp.org
```

Enter the server names you require, press Ctrl+O to write out the */etc/ntp.conf* file, then Ctrl+X to exit *nano*. Restart the *ntp* service with:

```
$ sudo service ntp restart
```

The server should respond:

```
* Stopping NTP server ntpd [ OK ]
* Starting NTP server ntpd [ OK ]
```

Then use the *ntpq -p* command to confirm that *ntp* is working. This command should produce output similar to the following screenshot:


```
daniel@office:~$ ntpq -p
=====
      remote           refid      st t when poll reach  delay  offset  jitter
=====
europium.canoni 193.79.237.14  2 u  49   64    3 131.386 141.365  1.328
dnscache-slough 213.222.193.35  2 u  45   64    3  23.594  84.480 31.209
ntp2.exa-networ 195.66.241.10   2 u  45   64    3  32.222  87.153 61.082
time.xilo.net   194.35.252.7   2 u  45   64    3  24.055  86.010 19.211
mantaray.netine 249.240.53.144  2 u  46   64    3  24.754  91.331 65.929
daniel@office:~$
```

Adjusting the server time zone


If your server is set to a different time zone than the one that you set during Airtime installation, your broadcast schedule may be played out at incorrect times. The data center which hosts your Airtime server could be located anywhere in the world. Some servers are set to Coordinated Universal Time or UTC (similar to Greenwich Mean Time or GMT), regardless of their location. If this is not appropriate for your station, on a Debian or Ubuntu server you can reconfigure the *tzdata* (time zone data) package with the command:

```
$ sudo dpkg-reconfigure tzdata
```

This command opens a menu in which you can select the continent that you require, by pressing the Enter key.



The next step is to select your nearest city, again by pressing the Enter key. The appropriate time zone is selected according to the information that you have entered.



The console output from the `dpkg-reconfigure tzdata` command will confirm the new setting.

```
Current default time zone: 'Europe/London'
Local time is now:      Mon Mar  7 15:04:58 GMT 2011.
Universal Time is now:  Mon Mar  7 15:04:58 UTC 2011.
```

Using the import script

If you have a large number of files in your media library, importing these files one at a time into a broadcast automation system would be time-consuming and tedious. That's why Airtime includes a script that can import an entire directory of files in one go.

Copying versus linking

You must specify one of two options for using the import script: Either to **copy** files into Airtime's storage server, or to **link** to files elsewhere. Each option has advantages and disadvantages, so you will have to think about how the files will be used in your station long-term.

- For files that are *copied*, you may run into problems with hard disk space if you do not remove files from the storage server periodically.
- For files that are *linked*, you must make sure that the files are actually going to be there at playout time, otherwise they will be skipped. For this reason, it is not recommended to use the link option for easily-removable storage (like MP3 players or USB memory sticks). There's a strong likelihood that the storage might be unplugged and taken away before playout time. It is also important to make sure that any external hard disk with linked files is powered on, and stays on.

The import script works from the command line, so you must first log into a console on the Airtime server. Then change to the *utils* directory beneath the directory where Airtime is installed, for example:

```
$ cd /var/lib/airtime/utils
```

You need to specify the full file system path to the media files that you wish to import. Copying is specified by including the *-c* switch in the command:

```
$ sudo ./airtime-import -c /<path>/<to>/<your>/<files>
```

Linking is specified by using the *-l* switch instead:

```
$ sudo ./airtime-import -l /<path>/<to>/<your>/<files>
```

If the import is successful, the script will report the names of the files imported.

```
daniel@office:/var/lib/airtime/utils$ sudo ./airtime-import -l /home/daniel/Music/strutsampler
[sudo] password for daniel:
=====
Airtime Import Script
=====
Importing: [00001] /home/daniel/Music/strutsampler/01 Love Dancing.mp3
Importing: [00002] /home/daniel/Music/strutsampler/02 Dat Soca Boat.mp3
Importing: [00003] /home/daniel/Music/strutsampler/03 My Oasis.mp3
Importing: [00004] /home/daniel/Music/strutsampler/04 Love And Death.mp3
Importing: [00005] /home/daniel/Music/strutsampler/05 (Do The) Spanish Hustle (Danny Krivit).mp3
Importing: [00006] /home/daniel/Music/strutsampler/06 Electricone.mp3
Importing: [00007] /home/daniel/Music/strutsampler/07 Cherchez Pas.mp3
Importing: [00008] /home/daniel/Music/strutsampler/08 Emakhaya.mp3
Importing: [00009] /home/daniel/Music/strutsampler/09 Wozani Mahipi.mp3
Importing: [00010] /home/daniel/Music/strutsampler/10 Green Africa.mp3
=====
*** Import mode: link
*** Files imported: 10
*** Duplicate files (not imported):
*** Total: 10 files in 3 seconds = 3.3 files/second.
=====
daniel@office:/var/lib/airtime/utils$
```

If you do not have write access to the filesystem, or the files are duplicates of files that have already been imported, the script will warn you with an error message.

Metadata quality

The *airtime-import* script automatically imports any metadata that is in the files' ID3 tags. If these tags are incorrect or are missing information, you will have to either edit the metadata before importing them, or suffer the consequences. For example, if the tags have artist or genre metadata missing, it will be impossible to search for, playlist or schedule the media according to these criteria.

The program **Audio Tag Tool** can be useful for batch setting and editing ID3 tags before importing files into your Airtime server. On an Ubuntu desktop machine, you can install Audio Tag Tool with the command:

```
$ sudo apt-get install tagtool
```

After installation, you can run the program with the command:

```
$ tagtool
```

The *Tag Multiple Files* feature of the Audio Tag Tool program is a particularly useful time saver if you have a large archive of untagged files. Sometimes there is artist or title information in the filename, which can be converted into an ID3 tag automatically.



USING AIRTIME

Getting started


If the Airtime server has a web browser installed, you can access the administration interface by opening the address:

`http://localhost/login`


If you have set up Airtime so that it can be accessed from other computers, you would use a domain name. For example:

`http://airtime.example.com/login`


You can log in for the first time with the username *admin* and password *admin*.



After you have logged in, you should see the **Master Panel**, which is present at the top of every page of the Airtime interface. On the left hand side, the Master Panel displays the details of the previous file played out, the current file playing (with an orange progress bar), and the next file due to play. It also displays the name and scheduled time of the current show, with a blue progress bar. Beneath this side of the Master Panel is the main navigation menu, with sub-menus labeled **Now Playing**, **Add Audio**, **Playlist Builder**, **Calendar**, **Configure** and **Help**. We'll be looking at the contents of these menus in the following chapters of this manual.



On the right hand side, the Master Panel features an **On Air** indicator, which turns from gray to red whenever a file is being played out. There is also a clock indicating the **Station time** and time zone. Over on the far side, an **About** link opens a pop-up window with some information about Airtime. The name of the user currently logged in is displayed, and below this there is the link to **Logout**.




On the **Configure** menu, click **Preferences** to set your **Station Name** and the **Default Fade** time that you would like to set for automated crossfades. Then click the **Submit** button.

Checking the stream

If you have enabled the streaming option when you installed Airtime, you can check that the Icecast server is running by opening port 8000 of the server in your web browser. For example, on the server itself, you can use:


`http://localhost:8000/`

You should see the Icecast status page, with details of the connection that Airtime has made to Icecast. If you have only just installed Airtime, there won't be any media playing out yet.




Managing users

You should set a new administrator password immediately, using the **Manage Users** entry on the **Configure** menu.



On the left hand side of the **Manage Users** page, click on *admin* in the user list. The details for this user will appear in the box on the right hand side. At the moment, the *admin* user only has a **Username** and a **Password**.



Enter a secure password (as long and as varied as is practical) into the **Password** field. Keeping this password secure is essential for the smooth running of your station, because it enables access to all scheduling and management features. You can also enter other details for your user account on this page, including your full name and contact details. Then click the **Submit** button.

The screenshot shows a web interface for adding a new user. On the left, there is a table with columns 'name' and 'Role'. The 'name' column has a magnifying glass icon, and the 'Role' column has a dropdown arrow. Below the table is a search bar. The main form area is titled 'New user' and contains the following fields:

- Username:** admin
- Password:** (masked with dots)
- Firstname:** Station
- Lastname:** Manager
- Email:** manager@example.com
- Skype:** broadcaster1000
- Jabber:** manager@example.com
- Role:** admin (selected from a dropdown menu)

A 'submit' button is located at the bottom right of the form.

To add further user accounts to the system, one for each of your station staff that need access to Airtime, click the **New user** button. Enter a username, password and contact details, and then select the user **Role** from the drop down menu, which can be *admin*, *host*, or *guest*. The difference between these roles is:

- An *admin* (station manager) has read and write access to all the features of Airtime. This role should be reserved for trusted staff members only.
- A *host* (presenter, or DJ) only has write access to features related to the specific shows assigned to them by an *admin*. The *host* can read data for other shows, but not write to them. This read access to other shows helps hosts plan their own shows, for instance avoiding the scenario where two DJs play the same music by coincidence.
- A *guest* can log in to read the forthcoming schedule or playlists, but has no write permission for any feature. The group of guests might include the station accountant, or the show assistants.

New users that you add will be shown in the list on the left-hand side of the **Manage Users** page. If you have a large number of users on the system, you can use the search tool above the list (which has a magnifying glass icon) to identify specific user accounts. Click on the list headings to sort the search results by *Username*, *Firstname*, *Lastname* or *Role*. To remove a user account, click the small **x** icon to the right side of its row in the list.

Now playing

This page provides two views of the files your station is playing, which can be switched using the **Day View** and **Now View** buttons in the top right corner of the administration interface. If you've only just installed Airtime, there won't be any files shown in either view yet.

The default is **Now View**, in which files that have already been played are removed from the top of the list. The row for the currently playing file is shown with an orange background. Any empty slots in the schedule are shown with a red background.

NOW PLAYING ADD AUDIO PLAYLIST BUILDER CALENDAR CONFIGURE ▾ HELP						
Date	Start	End	Duration	Song	Artist	
2011-03-17	16:25:00	16:31:01.29	00:06:01.29	Love Dancing	Arthur's Landing	Str
2011-03-17	16:31:01.29	16:35:19.66	00:04:18.37	Баллада № 1 (женский романс)	Ильмера	Сек
2011-03-17	16:35:19.66	16:39:02.32	00:03:42.66	WO QUI NON COIN / COWBOY BEBOP	Aoi Tada	Spa
2011-03-17	16:39:02.32	16:41:27.28	00:02:24.95	Respect	Aretha Franklin	I Ne Wa
2011-03-17	16:41:27.28	16:45:06.75	00:03:39.47	Cherry Blossom Girl	Air	Tall
2011-03-17	16:45:06.75	16:48:06.18	00:02:59.43	Seven Nation Army	Ben L'Oncle Soul	Ben
2011-03-17	16:48:06.18	16:52:01.57	00:03:55.39	Warlock	Desmond Dekker	Rock of D
2011-03-17	16:52:01.57	00:00:00	07:07:58.42	-	-	-


On the right hand side of the **Now View**, the **Playlist** and **Show** that each file is a part of is displayed. (Creating playlists and shows is covered in later chapters of this manual).

CALENDAR CONFIGURE ▾ HELP					Airtime 	
					Day View	Now View
Song	Artist	Album	Playlist	Show		
Love Dancing	Arthur's Landing	Strut Sampler 2011	My playlist	Test Show		
Баллада № 1 (женский романс)	Ильмера	Секреты	My playlist	Test Show		
WO QUI NON COIN / COWBOY BEBOP	Aoi Tada	Space Bio Charge	My playlist	Test Show		
Respect	Aretha Franklin	I Never Loved A Man the Way I Love You	My playlist	Test Show		
Cherry Blossom Girl	Air	Talkie Walkie	My playlist	Test Show		
Seven Nation Army	Ben L'Oncle Soul	Ben L'Oncle Soul	My playlist	Test Show		
Warlock	Desmond Dekker	Rockin' Steady The Best of Desmond Dekker	My playlist	Test Show		
-	-	-	-	-		


The **Day View** is similar to the **Now View**, except that files which have already played out are shown at the top of the window. You can select which day of the schedule you wish to view by clicking on the date box, just to the left of the **Day View** button, and selecting a day from the pop-up calendar.

Add audio


If you do not have access to the *airtime-import* script on the server, you can add files to the Airtime database using the **Add audio** page of the administration interface. This page includes an upload queue for files which supports drag and drop from your computer's file manager, if you are using the recommended *Firefox 3.6* web browser.




If your web browser does not support drag and drop, you can use the **Add files** button, which has a white plus sign in a green circle icon, to open a file selection window on your computer.




After you have added all the files that you require to the upload queue, click the **Start Upload** button, which has a green arrow icon.



The row of the file currently being uploaded is highlighted in pale green. At the bottom of the upload queue, a progress bar and percentage indicates how much of the upload has taken place so far.



Once it has been uploaded successfully, each file row displays a white check mark in a green circle icon.



The screenshot shows the Airtime software interface. At the top, the 'Airtime' logo is visible. Below it is a table with two columns: 'Size' and 'Status'. The table lists two files: an 8 MB file at 100% completion with a green checkmark, and a 7 MB file at 86% completion. A progress bar at the bottom indicates a total of 15 MB at 94% completion.

Size	Status
8 MB	100% 
7 MB	86%

15 MB 94%

Your files are now imported into the Airtime database, ready to be included in your broadcast playlist.

Playlist builder

This page of the Airtime interface enables you to search the media archive, sort and display the search results by the criteria that you choose, and drag and drop search results into an open playlist. You can also re-arrange the currently open playlist by dragging and dropping.

The Search tab

On the right hand side of the Playlist Builder page, the **Search** tab lists both the media and the playlists in the Airtime archive, with ten entries shown per page by default. Click on the **Show entries** drop-down menu in the top right corner to select the display of 10, 25, 50 or 100 entries per page, according to your preference.

Click the column headings **Title**, **Creator**, **Album**, **Track**, **Length** or **Type** to sort the entries. In the **Type** column, audio files are represented by a loudspeaker icon, while playlists are represented with a document icon. At the bottom of the window, click the **First**, **Previous**, **Next**, **Last** or page number buttons to browse the media archive.

Search					
			Show 10 entries		
◇ Title	◇ Creator	◇ Album	Track ▲	◇ Length	◇ Type
Panic	Ofir Gal	PANIC	1	00:03:27.464	🔊
Blue Orchid	The White Stripes	Get Behind Me Satan	1	00:02:37.56	🔊
Gulag Orkestar	Beirut	Gulag Orkestar	1	00:04:38.961	🔊
Seven Nation Army	Ben L'Oncle Soul	Ben L'Oncle Soul	1	00:02:59.43	🔊
Dayvan Cowboy	Boards of Canada	Trans Canada Highway	1	00:05:01.453	🔊
The High Road	Broken Bells	Broken Bells	1	00:03:52.254	🔊
Who Was In My Room Last Night?	Butthole Surfers	Independent Worm Saloon	1	00:04:09.38	🔊
Blue Rondo A La Turk	The Dave Brubek Quartet	Time Out	1	00:06:46.177	🔊
Balrog Boogie	Diablo Swing Orchestra	The Butcher's Ballroom	1	00:03:53.186	🔊
Bombay	El Guincho	Pop Negro	1	00:03:39.324	🔊
Showing 1 to 10 of 555 entries					
First	Previous	1	2	3	4
			5	Next	Last

Type a search term into the box in the upper left corner, with the magnifying glass icon. Like an Internet search engine, the filtered entries shown are refined as you type - there is no need to press the Enter key.

ON AIR

Station time
13:10:19
UTC

HELP

Search

Show 10

Title	Creator	Album	Track	Length	
Love Dancing	Arthur's Landing	Strut Sampler 2011	1	00:06:01.299	
Dat Soca Boat	Mighty Shadow	Strut Sampler 2011	2	00:04:49.985	

Showing 1 to 2 of 2 entries (filtered from 555 total entries)

First

Previous

1

Next

Last

Creating a new playlist

Once you have found the media that you require using the **Search** tab, you can create a new playlist on the left hand side of the **Playlist Builder** page. Click the **New** button to begin.

NOW PLAYING

ADD AUDIO

PLAYLIST BUILDER

CALENDAR

CONFIGURE

New

No open playlist

Enter a **Title** and **Description** for the playlist, then click the **Submit** button. Setting good quality metadata here will help you find the playlist using the **Search** tab later, so you should be as descriptive as possible.

NOW PLAYING

ADD AUDIO

PLAYLIST BUILDER

CALENDAR

CONFIGURE


Playlist Metadata

Title:


Description:

Submit


Next, drag and drop files from the Search tab into the new playlist.




After dragging files into the new playlist, the total playlist time is displayed in the top left corner. Durations for individual files are shown in each row of the playlist. Click the small x icon on the right hand side of each row to remove a file from the playlist. You can also drag and drop files to re-order them.




Click the playlist **Crossfade** button (two horizontal white arrows crossing in a gray rectangle), to the right of the **New** and **Delete** buttons, to open a beige bar in which you can set the **Fade in** and **Fade out** times for this playlist.



Click any one of the smaller **Crossfade** buttons between file rows to open a bar which enables you to set fade in and fade out times between two adjacent files in the playlist.




When your playlist is complete, click the **Done Editing** button. If you want to edit the playlist contents or the playlist metadata later, you can find it by **Title** or **Creator** using the **Search** tab. Right-click on the playlist in the search results list, and select **Edit** or **Edit Metadata** from the pop-up context menu. You can also **Delete** a playlist from this context menu.




Calendar

This page of the Airtime administration interface has three views: **Day**, **Week** and **Month**, which can be switched using the gray buttons in the top right corner. By default, the **Month** view is shown, with today's date highlighted by a beige background.



In the top left corner of the page, you can go back or forward through the **Calendar** by clicking on the small white triangle buttons. Click the **Today** button to jump to today's date in the current view. In the **Day** or **Week** views, there is also a drop-down menu which allows you to set the resolution displayed for the calendar, ranging from five minutes per row to sixty minutes per row.



Adding a show

To add a new show to the calendar, click the **+ Show** button in the top left corner of the page, or click on any empty slot in the **Calendar** itself. Either of these actions opens the **Add this show** box, which has four sections, arranged vertically: **What**, **When**, **Who**, and **Style**. Click the small black triangle to the left of the section name if you wish to minimize it.

In the **What** box, enter the name and description for the show that you are creating.

Close Add this show

► What

Name:
Test Show

Description:
This is an example show.

Next, in the **When** section, the date that you clicked on in the **Calendar** should already be entered in the **Date Start** field. To set another date for the show, click on the **Date Start** field and then select the alternative date that you require for the show from the small pop-up calendar. Then set the **Start time** and **Duration** for the show in the same way, with the pop-up **Hour** and **Minute** box. The minute values in the pop-up time boxes are rounded to the nearest five minutes, but you can adjust the times manually by clicking into the fields and typing.

► When

Date Start: 2011-03-18

Start Time: 12:30

Duration:

	Hour						Minute		
AM	00	01	02	03	04	05	00	05	10
	06	07	08	09	10	11	15	20	25
PM	12	13	14	15	16	17	30	35	40
	18	19	20	21	22	23	45	50	55

repeats

► Who

Type a Host:

To schedule a regular show, check the **Repeats** box and select either **Weekly**, **Bi-weekly** or **Monthly** from the **Repeat Type** drop-down menu that will appear. Then check the boxes for the days of the week that you want to schedule the regular show on. Set the **Date End** for the regular show to finish, or check the **No End** box to schedule the show indefinitely.

► **When**

Date Start: 2011-03-18

Start Time: 12:29

Duration: 00:31

repeats ☒

Repeat Type: weekly

Select Days:

☐ Sun ☒ Mon ☒ Tue ☒ Wed ☒ Thu ☒ Fri ☐ Sat

Date End: 2012-03-19

no end

► **Who**

Type a Host:

Hosts:

☐ klajn

March 2012

Su	Mo	Tu	We	Th	Fr	Sa
				1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	31

In the **Who** section, type the first few letters of the name of the show presenter to select a name from the database, or check one of the boxes in the vertical scrolling list below.

► **Who**

Type a Host: ada

Hosts:

☐ ccruz

☒ katerina

☐ klajn

Finally, select a **Background Colour** and **Text Colour** from the **Style** section, so that the new show can be easily identified in the **Calendar**.

Hosts:

☒ adam

☐ ccruz

☒ katerina

☐ klajn

► **Style**

Background Colour:

Text Colour: 3d173d

Color picker interface showing a gradient bar and color selection tools.

Click the **Add this show** button at the top of the box. The new show will now be displayed in the **Calendar**, with a regular slot if you have chosen to schedule one.

Airtime

March 2011

day


week

month


Tue	Wed	Thu	Fri	Sat
1	2	3	4	5
				9:00 - 10:00 One hour for soul
8	9	10	11	12
11:34 100 wonderful songs 12:34 One hour for soul 14:04 Fire 15:04 Listen	2:00 - 4:00 Preslav Literary Show 10:00 - 11:34 100 wonderful songs 11:34 - 12:34 One hour for soul 12:34 - 14:04 Fire lunch	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 10:00 - 11:04 100 wonderful songs 11:04 - 13:04 One hour for soul 13:04 - 14:04 Fire lunch	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 10:00 - 12:04 100 wonderful songs 12:04 - 14:04 Fire lunch	2:00 - 4:00 Preslav Literary Show
15	16	17	18	19
1:00 Art Nightwatch 4:00 Preslav Literary Show	2:00 - 4:00 Preslav Literary Show	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 16:25 - 16:55 Test Show	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 13:10 - 13:41 Test Show	
22	23	24	25	26
1:00 Art Nightwatch 4:00 Preslav Literary Show 13:41 Test	2:00 - 4:00 Preslav Literary Show 13:10 - 13:41 Test Show	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 13:10 - 13:41 Test Show	0:00 - 1:00 Art Critic's Nightwatch 2:00 - 4:00 Preslav Literary Show 13:10 - 13:41 Test Show	

Adding content to a show


To add content to a show, right-click on it in the Calendar, and select Add Content from the pop-up context menu.



This action opens the **Schedule Playlist** pop-up window. Just like when using the **Playlist Builder** to find files, you can search for playlists and drag them into the **Items in this Show** box.



The orange progress bar underneath the **Items in this Show** box updates automatically to show how much time remains from the allocated show duration. Click the small white triangle on the left of each row to see details of the playlist, or click the white x icon on the right side to remove it from the show.




When your show has all the required content, click the **OK** button in the bottom right corner to close the window. Back in the **Calendar**, right-click on the show and select **Show content** from the pop-up context menu to view a list of content now included in the show. Click the **OK** button in the bottom right corner, or the x icon in the top right corner, to close this window.

Show Contents					
Start	Title	Creator	Album	Length	Genre
2011-03-21 13:10:00	Love Dancing	Arthur's Landing	Strut Sampler 2011	00:06:01.299	
2011-03-21 13:16:01.299	Баллада № 1 (женский романс)	Ильмера	Секреты	00:04:18.37	Blues
2011-03-21 13:20:19.669	WO QUI NON COIN / COWBOY BEBOP	Aoi Tada	Space Bio Charge	00:03:42.66	Anime
2011-03-21 13:24:02.329	Respect	Aretha Franklin	I Never Loved A Man the Way I Love You	00:02:24.953	Oldies
2011-03-21 13:26:27.282	Cherry Blossom Girl	Air	Talkie Walkie	00:03:39.472	Other
2011-03-21 13:30:06.754	Seven Nation Army	Ben L'Oncle Soul	Ben L'Oncle Soul	00:02:59.43	R&B
2011-03-21 13:33:06.184	Warlock	Desmond Dekker	Rockin' Steady The Best of Desmond Dekker	00:03:55.391	Ska
					Ok

Removing content from a show

To remove an individual playlist from a show, right-click on the show in the **Calendar**, and select **Add Content** from the pop-up menu. In the **Schedule Playlist** window which opens, use the white x icon to remove the playlist from the show content. To remove all playlists from a show, right-click on the show in the **Calendar**, and select **Remove All Content** from the pop-up menu.




Deleting a show

To delete one instance of a regular show, right-click on the show in the **Calendar**, and select **Delete this instance** from the pop-up menu. If you wish to delete all future instances of this particular show, select **Delete this instance and all following** from the pop-up menu.

You cannot delete or remove content from shows that have already played out. These shows have only one option on the pop-up menu, which is **Show content**.

Help

The Help menu in Airtime offers a 'quick start' guide for new users.



You can visit the Airtime online support forum, and sign up for the mailing list, at <http://forum.sourcefabric.org/index.php/f/14/>

This forum is mirrored by the mailing list, so posts on the forum appear on the mailing list and vice versa. You can therefore also post a message there by emailing airtime-support@lists.sourcefabric.org

To subscribe to forum updates via mail, please register or login to the forum by clicking the appropriate link. Then click the 'Subscribe' button at the top of each forum page.

Bug reporting

Airtime needs your input to improve. If you think you've found a bug, please visit <http://dev.sourcefabric.org/> and sign in, using the same login and password that you registered for the Airtime forum. Create a bug report by selecting **Create Issue**, then **Airtime**, and then **Bug**. That way, the Airtime team can keep track of your problem and notify you when it has been fixed. You can also suggest improvements and new features for Airtime on that site.

Contact

Finally, when all other avenues have been exhausted, email us directly at contact@sourcefabric.org and we'll try to help!

Other help

The UNESCO wiki *Community Radio - A user's guide to the technology*: <http://cr-userguide.web4all.in/> features a very comprehensive guide to setting up a community radio station. This guide is aimed at people thinking about setting up a radio station in India, but includes lots of practical advice that would be useful in any country.

APPENDIX

Time zones

Use the appropriate time zone value from the list below in the *php.ini* file on your Airtime server.

Africa

Africa/Abidjan
Africa/Accra
Africa/Addis_Ababa
Africa/Algiers
Africa/Asmara
Africa/Asmera
Africa/Bamako
Africa/Bangui
Africa/Banjul
Africa/Bissau
Africa/Blantyre
Africa/Brazzaville
Africa/Bujumbura
Africa/Cairo
Africa/Casablanca
Africa/Ceuta
Africa/Conakry
Africa/Dakar
Africa/Dar_es_Salaam
Africa/Djibouti
Africa/Douala
Africa/El_Aaiun
Africa/Freetown
Africa/Gaborone
Africa/Harare
Africa/Johannesburg
Africa/Kampala
Africa/Khartoum
Africa/Kigali
Africa/Kinshasa
Africa/Lagos
Africa/Libreville
Africa/Lome
Africa/Luanda
Africa/Lubumbashi
Africa/Lusaka
Africa/Malabo
Africa/Maputo
Africa/Maseru
Africa/Mbabane
Africa/Mogadishu
Africa/Monrovia
Africa/Nairobi
Africa/Ndjamena
Africa/Niamey
Africa/Nouakchott
Africa/Ouagadougou
Africa/Porto-Novo
Africa/Sao_Tome
Africa/Timbuktu
Africa/Tripoli
Africa/Tunis
Africa/Windhoek

America

America/Adak
America/Anchorage
America/Anguilla
America/Antigua
America/Araguaina
America/Argentina/Buenos_Aires
America/Argentina/Catamarca
America/Argentina/ComodRivadavia
America/Argentina/Cordoba
America/Argentina/Jujuy
America/Argentina/La_Rioja
America/Argentina/Mendoza
America/Argentina/Rio_Gallegos
America/Argentina/Salta
America/Argentina/San_Juan
America/Argentina/San_Luis
America/Argentina/Tucuman
America/Argentina/Ushuaia
America/Aruba
America/Asuncion
America/Atikokan
America/Atka
America/Bahia
America/Bahia_Banderas
America/Barbados
America/Belem
America/Belize
America/Blanc-Sablon
America/Boa_Vista
America/Bogota
America/Boise
America/Buenos_Aires
America/Cambridge_Bay
America/Campo_Grande
America/Cancun
America/Caracas
America/Catamarca
America/Cayenne
America/Cayman
America/Chicago
America/Chihuahua
America/Coral_Harbour
America/Cordoba
America/Costa_Rica
America/Cuiaba
America/Curacao
America/Danmarkshavn
America/Dawson
America/Dawson_Creek
America/Denver
America/Detroit
America/Dominica
America/Edmonton
America/Eirunepe
America/El_Salvador
America/Ensenada
America/Fort_Wayne
America/Fortaleza
America/Glace_Bay
America/Godthab
America/Goose_Bay
America/Grand_Turk
America/Grenada
America/Guadeloupe
America/Guatemala
America/Guayaquil
America/Guyana
America/Halifax
America/Havana
America/Hermosillo

America/Indiana/Indianapolis
America/Indiana/Knox
America/Indiana/Marengo
America/Indiana/Petersburg
America/Indiana/Tell_City
America/Indiana/Vevay
America/Indiana/Vincennes
America/Indiana/Winamac
America/Indianapolis
America/Inuvik
America/Iqaluit
America/Jamaica
America/Jujuy
America/Juneau
America/Kentucky/Louisville
America/Kentucky/Monticello
America/Knox_IN
America/La_Paz
America/Lima
America/Los_Angeles
America/Louisville
America/Maceio
America/Managua
America/Manaus
America/Marigot
America/Martinique
America/Matamoros
America/Mazatlan
America/Mendoza
America/Menominee
America/Merida
America/Mexico_City
America/Miquelon
America/Moncton
America/Monterrey
America/Montevideo
America/Montreal
America/Montserrat
America/Nassau
America/New_York
America/Nipigon
America/Nome
America/Noronha
America/North_Dakota/Beulah
America/North_Dakota/Center
America/North_Dakota/New_Salem
America/Ojinaga
America/Panama
America/Pangnirtung
America/Paramaribo
America/Phoenix
America/Port-au-Prince
America/Port_of_Spain
America/Porto_Acre
America/Porto_Velho
America/Puerto_Rico
America/Rainy_River
America/Rankin_Inlet
America/Recife
America/Regina
America/Resolute
America/Rio_Branco
America/Rosario
America/Santa_Isabel
America/Santarem
America/Santiago
America/Santo_Domingo
America/Sao_Paulo
America/Scoresbysund
America/Shiprock
America/St_Barthelemy
America/St_Johns

America/St_Kitts
America/St_Lucia
America/St_Thomas
America/St_Vincent
America/Swift_Current
America/Tegucigalpa
America/Thule
America/Thunder_Bay
America/Tijuana
America/Toronto
America/Tortola
America/Vancouver
America/Virgin
America/Whitehorse
America/Winnipeg
America/Yakutat
America/Yellowknife

Antarctica

Antarctica/Casey
Antarctica/Davis
Antarctica/DumontD'Urville
Antarctica/Macquarie
Antarctica/Mawson
Antarctica/McMurdo
Antarctica/Palmer
Antarctica/Rothera
Antarctica/South_Pole
Antarctica/Syowa
Antarctica/Vostok

Arctic

Arctic/Longyearbyen

Asia

Asia/Aden
Asia/Almaty
Asia/Amman
Asia/Anadyr
Asia/Aqtau
Asia/Aqtobe
Asia/Ashgabat
Asia/Ashkhabad
Asia/Baghdad
Asia/Bahrain
Asia/Baku
Asia/Bangkok
Asia/Beirut
Asia/Bishkek
Asia/Brunei
Asia/Calcutta
Asia/Choibalsan
Asia/Chongqing
Asia/Chungking
Asia/Colombo
Asia/Dacca
Asia/Damascus
Asia/Dhaka
Asia/Dili
Asia/Dubai
Asia/Dushanbe
Asia/Gaza
Asia/Harbin
Asia/Ho_Chi_Minh
Asia/Hong_Kong
Asia/Hovd
Asia/Irkutsk
Asia/Istanbul
Asia/Jakarta
Asia/Jayapura
Asia/Jerusalem
Asia/Kabul
Asia/Kamchatka
Asia/Karachi
Asia/Kashgar
Asia/Kathmandu
Asia/Katmandu
Asia/Kolkata
Asia/Krasnoyarsk
Asia/Kuala_Lumpur
Asia/Kuching
Asia/Kuwait
Asia/Macao
Asia/Macau
Asia/Magadan
Asia/Makassar
Asia/Manila
Asia/Muscat
Asia/Nicosia
Asia/Novokuznetsk
Asia/Novosibirsk
Asia/Omsk
Asia/Oral
Asia/Phnom_Penh
Asia/Pontianak
Asia/Pyongyang
Asia/Qatar
Asia/Qyzylorda
Asia/Rangoon
Asia/Riyadh
Asia/Saigon
Asia/Sakhalin
Asia/Samarkand
Asia/Seoul
Asia/Shanghai

Asia/Singapore
Asia/Taipei
Asia/Tashkent
Asia/Tbilisi
Asia/Tehran
Asia/Tel_Aviv
Asia/Thimbu
Asia/Thimphu
Asia/Tokyo
Asia/Ujung_Pandang
Asia/Ulaanbaatar
Asia/Ulan_Bator
Asia/Urumqi
Asia/Vientiane
Asia/Vladivostok
Asia/Yakutsk
Asia/Yekaterinburg
Asia/Yerevan

Atlantic Ocean

Atlantic/Azores
Atlantic/Bermuda
Atlantic/Canary
Atlantic/Cape_Verde
Atlantic/Faeroe
Atlantic/Faroe
Atlantic/Jan_Mayen
Atlantic/Madeira
Atlantic/Reykjavik
Atlantic/South_Georgia
Atlantic/St_Helena
Atlantic/Stanley

Europe

Europe/Amsterdam
Europe/Andorra
Europe/Athens
Europe/Belfast
Europe/Belgrade
Europe/Berlin
Europe/Bratislava
Europe/Brussels
Europe/Bucharest
Europe/Budapest
Europe/Chisinau
Europe/Copenhagen
Europe/Dublin
Europe/Gibraltar
Europe/Guernsey
Europe/Helsinki
Europe/Isle_of_Man
Europe/Istanbul
Europe/Jersey
Europe/Kaliningrad
Europe/Kiev
Europe/Lisbon
Europe/Ljubljana
Europe/London
Europe/Luxembourg
Europe/Madrid
Europe/Malta
Europe/Mariehamn
Europe/Minsk
Europe/Monaco
Europe/Moscow
Europe/Nicosia
Europe/Oslo
Europe/Paris
Europe/Podgorica
Europe/Prague
Europe/Riga
Europe/Rome
Europe/Samara
Europe/San_Marino
Europe/Sarajevo
Europe/Simferopol
Europe/Skopje
Europe/Sofia
Europe/Stockholm
Europe/Tallinn
Europe/Tirane
Europe/Tiraspol
Europe/Uzhgorod
Europe/Vaduz
Europe/Vatican
Europe/Vienna
Europe/Vilnius
Europe/Volgograd
Europe/Warsaw
Europe/Zagreb
Europe/Zaporozhye
Europe/Zurich

Indian Ocean

Indian/Antananarivo
Indian/Chagos
Indian/Christmas
Indian/Cocos
Indian/Comoro
Indian/Kerguelen
Indian/Mahe
Indian/Maldives
Indian/Mauritius
Indian/Mayotte
Indian/Reunion

Pacific Ocean

Pacific/Apia
Pacific/Auckland
Pacific/Chatham
Pacific/Chuuk
Pacific/Easter
Pacific/Efate
Pacific/Enderbury
Pacific/Fakaofu
Pacific/Fiji
Pacific/Funafuti
Pacific/Galapagos
Pacific/Gambier
Pacific/Guadalcanal
Pacific/Guam
Pacific/Honolulu
Pacific/Johnston
Pacific/Kiritimati
Pacific/Kosrae
Pacific/Kwajalein
Pacific/Majuro
Pacific/Marquesas
Pacific/Midway
Pacific/Nauru
Pacific/Niue
Pacific/Norfolk
Pacific/Noumea
Pacific/Pago_Pago
Pacific/Palau
Pacific/Pitcairn
Pacific/Pohnpei
Pacific/Ponape
Pacific/Port_Moresby
Pacific/Rarotonga
Pacific/Saipan
Pacific/Samoa
Pacific/Tahiti
Pacific/Tarawa
Pacific/Tongatapu
Pacific/Truk
Pacific/Wake
Pacific/Wallis
Pacific/Yap

About this manual

Copyright (C) 2011 Sourcefabric o.p.s

This manual was written for Sourcefabric by Daniel James, using the tools at FLOSS Manuals. Please add your comments and contributions at: <http://en.flossmanuals.net/airtime/>

This documentation is free documentation; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, version 3.

This documentation is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this documentation; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

“Copyright” also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

“The Program” refers to any copyrightable work licensed under this License. Each licensee is addressed as “you”. “Licensees” and “recipients” may be individuals or organizations.

To “modify” a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a “modified version” of the earlier work or a work “based on” the earlier work.

A “covered work” means either the unmodified Program or a work based on the Program.

To “propagate” a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To “convey” a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays “Appropriate Legal Notices” to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The “source code” for a work means the preferred form of the work for making modifications to it. “Object code” means any non-source form of a work.

A “Standard Interface” means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The “System Libraries” of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A “Major Component”, in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The “Corresponding Source” for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A “User Product” is either (1) a “consumer product”, which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, “normally used” refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

“Installation Information” for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

“Additional permissions” are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered “further restrictions” within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An “entity transaction” is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A “contributor” is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's “contributor version”.

A contributor's “essential patent claims” are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, “control” includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a “patent license” is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To “grant” such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. “Knowingly relying” means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is “discriminatory” if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License “or any later version” applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

Made with Booki

Visit <http://software.booki.cc>

